

Tutti i modelli / All models: F80C - F120 - F125C - F200 - SF300 - SF500 - SFN1000 - SFN2200

Dati Tecnici - Specifications

	cond	comp. W	ABS. W	Fuse	Kwh/100Kg	l / h	kg	Lbs	kg	Lbs	Ton CO2 equiv.
SFN2200 A		10000	6100	25	7.4	77.1	362	796	383	843	9.63
SFN2200 W		10000	5800	32	7.4	416.7	362	796	383	843	9.63

24h Produzione Ghiaccio - Ice Production (kg/lbs)


Raffreddamento ad aria - Air Cooled Unit

Temp. aria Air Temp.	Temp. acqua / Water Temp.			
°C	32°	21°	15°	10°
°F	90°	70°	60°	50°
10°	2200			
50°	4840			
21°	2400			
70°	5280			
32°	1850			
90°	4078			
38°				
100°				


Raffreddamento ad acqua - Water Cooled Unit

Temp. aria Air Temp.	Temp. acqua / Water Temp.			
°C	32°	21°	15°	10°
°F	90°	70°	60°	50°
10°	2200			
50°	4840			
21°	2400			
70°	5280			
32°	1850			
90°	4078			
38°				
100°				


Vista frontale
Front view




Vista laterale
Lateral view



Vista posteriore
Rear view



Vista superiore
Top view



A Alimentazione elettrica
Electrical cable supply

B Entrata acqua 3/4" gas
Water inlet 3/4" gas

C Scarico acqua
Water drain ø 20 mm

D Entrata acqua - raffr. acqua 3/4" gas
Water inlet - cooled unit 3/4" gas

E Scarico bacinella 3/4" gas
Overflow drain 3/4" gas



PANNELLO DI CONTROLLO - CONTROL PANEL



DEPOSITO - SLOPE BIN

UD1000-DR620


DIMENSIONI - DIMENSIONS

LxPxH(mm): 1080 x 780 x 1255
WxDxH(in): 42 8/16" x 30 1/16" x 49 6/16"

DATI SPEDIZIONE / SHIPPING DATA

LxPxH(mm): 1170 x 920 x 1340
WxDxH(in): 46" 1/16 x 36" 4/16 x 52" 12/16

TIPO GHIACCIO - ICE TYPE



PERCENTUALE ACQUA RESIDUA 15-18%
ICE CONTAINS 15-18% RESIDUAL WATER

CONDIZIONI USO-OPERATING REQUIREMENTS

Calore espulso / Rejected Heat 19100 W

Volume aria / Air Volume 7000 m³/h



400V/3N/50Hz



R452a GWP=2141

MIN		MAX
30 µS/cm		500 µS/cm
10°C (50°F)		40°C (104°F)
10°C (50°F)		35°C (95°F)
- 10 %		+ 10 %
1 Bar (14 psi)		5 Bar (70 psi)

SFN2200 400V/3N/50HZ - Ice Flaker